

What is claimed is:

1. A tubing probe for measuring a volatile compound in a fluid contained in an enclosure, comprising:
  - 5 a probe body made of a single piece of metal;  
inlet and outlet channels provided in the probe body;  
a gas permeable tube attached to one end of the probe body to form a continuous passage for a carrier gas between the inlet and outlet channels;  
a sealing mechanism between the enclosure and the probe body for  
10 isolation of inside of the enclosure, and  
the probe body for positioning substantially only the gas permeable tube inside the enclosure so that when the probe is inserted into the enclosure, the volatile compound pervaporates into the gas permeable tube.
- 15 2. The tubing probe according to claim 1, further comprising:  
a supporting plate attached to the one end of the probe body for supporting the gas permeable tube.
3. The tubing probe according to claim 2, wherein the supporting plate  
20 includes a plurality of holes to which the gas permeable tube is threaded.
4. The tubing probe according to claim 1, further comprising:  
tube adaptors attached at the one end of the probe body to which each  
end of the gas permeable tube is secured.  
25
5. The tubing probe according to claim 4, further comprising:  
the tube adaptors are larger in the outside diameter than the inside  
diameter of the gas permeable tube.
- 30 6. The tubing probe according to claim 1, wherein the sealing mechanism comprises a shoulder on the probe body, so that, when inserted, a standard fermenter nut port locks the probe in place and ensures that substantially only the gas permeable tube is located inside the enclosure.
- 35 7. The tubing probe according to claim 6, wherein the sealing mechanism further comprises an O-ring to ensure sterility of the enclosure.

8. The tubing probe according to claim 1, further comprising:  
a carrier gas supply tube connected to the inlet channel, and a volatile  
detector connected to the outlet channel.

5 9. The tubing probe according to claim 8, further comprising:  
the probe body having a head at another end, to which head a  
detachable detector head-set can be attached.

10 10. The tubing probe according to claim 1, wherein the gas permeable tube  
is made of a material which is permeable to a volatile of interest.

15 11. The tubing probe according to claim 10, wherein the gas permeable  
tube is adjusted in length and diameter to optimise the performance of the  
probe in relation to the volatile of interest and environment in which to  
operate.

12. The tubing probe according to claim 10, wherein the material of the gas  
permeable tube is silicone.

20 13. The tubing probe according to claim 4, wherein each tube adaptor is  
configured in two sections, the tube section to receive one end of the gas  
permeable tube and another section to be welded to one end of the probe  
body.

25 14. The tubing probe according to claim 3, wherein the supporting plate  
has a plurality of holes so that a gas permeable tube of various length and  
size can be threaded.

30 15. The tubing probe according to claim 1, wherein the probe body is  
designed to fit in a standard 25 mm port of the enclosure.

35 16. The tubing probe according to claim 1, wherein the enclosure is a  
bioreactor or a fermenter.